



Surface luminaire with IP54

MODUS KX 8000, 1500mm, LED 840, opal cover, surface, not dimable, 1750mA DALI

Code: KX8000L4KO/DALI

EAN: 8596099060602



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP54
Color housing:	White	Suitable for suspended mounting:	Yes
Material housing:	Steel	Suitable for wall mounting:	Yes
Suitable for surface mounting:	Yes	Suitable for ceiling mounting:	Yes

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	8200
System power (W):	58	Luminaire efficacy (lm/W):	141
Color temperature (K):	4000	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	1500	Width (mm):	110
Height/depth (mm):	60	Built-in length (mm):	1200
Size version:	L	Weight (kg):	3

Elektrické vlastnosti

Protection class:	I	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
Dimming DALI:	Yes		