



LED panel with aluminium frame

MODUS Q, LED panel, recessed/pendant, LED 838, rectangle C, driver 700mA nondimmable

Code: Q3C600/700ND
EAN: 8595073793383



Vlastnosti svítidla

Product category:	Ceiling / wall luminaires	Degree of protection (IP):	IP40
Color housing:	Aluminium	Suitable for suspended mounting:	Yes
Material housing:	Aluminium	Suitable for built-in mounting:	Yes

Světelný zdroj

Lamp type:	LED not exchangeable	Effective luminous flux (lm):	4000
System power (W):	35	Luminaire efficacy (lm/W):	114
Color temperature (K):	3800	Color rendering index CRI:	80-89
Rated life time L80/B50 (h):	80000	With lamp:	Yes
Colour of light:	White		
Energy efficiency class of the built-in lamp:	A++, A+, A (LED)		

Optický systém

Optical system:	KO	Light outlet:	Direct
Light sharing:	Symmetric	Material cover:	Plastic, opal
Radiation angle:	Extreme wide beam >80°		

Rozměry

Length (mm):	1196	Width (mm):	296
Height/depth (mm):	15	Built-in height/depth (mm):	15
Raster (mm):	600	Size version:	M
Weight (kg):	4,8		

Elektrické vlastnosti

Protection class:	II	Connection type:	Pinching contact
Voltage type:	AC	Type of control gear:	LED operating device current-controlled
Nominal voltage (V):	220...240	Control gear included:	Yes
No dim function:	Yes		